



## An economy heat pump designed to fit any budget

- Compact unit has a small footprint
- · Vinyl coated evaporator coil and fan grill
- Microprocessor controlled automatic defrost
- Environmentally friendly R410A refrigerant

 ThermoLink Titanium heat exchanger with patented counter-flow water management for superior efficiency





	T35	T55	T75	
BTUs				
80/80/80*	35,000	50,000	73,000	
80/80/63**	32,000	46,000	67,500	
80/50/63**	18,000	25,000	42,000	
Coefficient of Performance				
80/80/80*	5.8	5.8	5.3	
80/80/63**	5.4	5.6	5.1	
80/50/63**	3.6	3.7	3.6	
Refrigerant	R410A	R410A	R410A	
Electrical				
Voltage/Hz/Phase	208-230/60/1	208-230/60/1	208-230/60/1	
Minimum Circuit Ampacity	19.43	19.43	26.14	
Maximum Fuse Size	30	30	45	
Water Flow				
Minimum/Maximum (gpm)	20/70	20/70	20/70	
Physical				
Shipping Weight (lbs)	215	215	250	
Size (LxWxH)	36"x24"x25"	36"x24"x25"	36"x24"x31"	

<sup>\* -</sup> ratings outside the scope of the ARI standard 1160 water temp/ambient air/relative humidity

<sup>\*\* -</sup> rated in accordance with ARI standard 1160 water temp/ambient air/relative humidity

Heater Model	<b>Pool Gallons</b>	5° rise	10° rise	15° rise	20° rise	25° rise	30° rise
T-35	5,000						
T-55	7,500						
T-75	10,000						
HWSQ	12,000						
	15,000						